



## **CHEMAX ANTICOR ACT 200**

**water base anti-rust compound for metal surface**

**CHEMAX ANTICOR ACT 200** is water based Anti-Rust Compound. It is ready to use Rust Preventing, no evaporative, Non-inflammable liquid. It also **increases the bonding strength** to the applied material about **300%**, thus giving it an extended strength & life to the material.

### **Technical Specification:**

Appearance: Light yellow

Sp. Gravity: 1.28 gm/cm

Coverage Area: 250 to 300 sq. ft/ltr (depending on surface)

Curing Time: Touch dry – 30 min. & hard dry- 24 hrs Application

Method: Brush/spray/dip

### **Application Area:**

CHEMAX ANTICOR ACT 200 is specially designed for protecting Steel from rust and external corrosion, and can be Extensively used in civil, building & construction, iron & steel, chemical & oil industry, Automobile & railways, defense Industry, industrial & domestic industry, Electricity board & pipe manufacturing industry.

### **Application method:**

- 1] The surface to be applied should be cleaned and free from any rust, dust, dirt, grease, oil & old paints.
- 2] When it is applied on the rusted surface, the color gradually changes & white spots occurred (because of rust) Indicating that the chemical reaction has taken place .The white portion can then be wiped & washed off with water And kept to dry.
- 3] The applied surface kept it open for dry for 30 minutes under normal weather condition and then further for 24 hrs to completely cure & make it rust proof.
- 4] It can be painted further with any Synthetic Enamel, Epoxy, Polycoat which will bond with the applied Surface more strongly because of the greater adhesions properties of ACT 200.
- 5] The application of Red Oxide primer is not necessary after applying CHEMAX ANTICOR ACT 200
- 6] Always pour / unload ACT 200 chemical only in a PVC / Plastic container and not in any other metallic Container.
- 7] Always wear Hand Gloves, Eye Goggles while using ACT 200

**Storage:** Up to six months in original sealed containers. Avoid direct exposure to light.

**Packing:** 500Gms, 1kg, 5kgs, 20kgs, 200kgs.